

Rangers





	 RANGER™ 4x4	 RANGER XP™	 RANGER HD™	 RANGER CREW™	 RANGER 6x6	 RANGER RZR™	 RANGER RZR S
Engine							
Displacement/HP	499cc/32 hp	683cc/40 hp	683cc/40 hp	683cc/40 hp	683cc/40 hp	760cc	760cc H.O.
Cooling	Liquid-cooled	Liquid-cooled	Liquid-cooled	Liquid-cooled	Liquid-cooled	Liquid-cooled	Liquid-cooled
Engine Type	4-valve, 4-stroke single cyl.	4-valve, 4-stroke twin cyl.	4-valve, 4-stroke twin cyl.	4-valve, 4-stroke twin cyl.	4-valve, 4-stroke twin cyl.	Twin cyl.	Twin cyl.
Top Speed	41 mph	50 mph	50 mph	44 mph	44 mph	55 mph	63 mph
Lubrication	Dry sump	Wet sump	Wet sump	Wet sump	Wet sump	Wet sump	Wet sump
Oil Capacity	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.
Carburetion	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Fuel Capacity	9.0 gal./34 ltr.	9.0 gal./34 ltr.	9.0 gal./34 ltr.	9.0 gal./34 ltr.	9.0 gal./34 ltr.	7.25 gal./27.4 ltr.	7.25 gal./27.4 ltr.
Coolant Capacity	2.3 qts./2 ltr.	3.25 qts./3 ltr.	3.25 qts./3 ltr.	3.3 qts./3 ltr.	3.3 qts./3 ltr.	4.8 qts./4.5 ltr.	4.8 qts./4.5 ltr.
Alternator	250 watts	500 watts	500 watts	500 watts	500 watts	500 watts	500 watts
Starting/Battery	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH
Drivetrain							
Transmission	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic PVT	Automatic PVT
Gear Range	In-line	In-line	In-line	In-line	In-line	In-line P/R/N/L/H	In-line P/R/N/L/H
Drive	4-wheel shaft drive	4-wheel shaft drive	4-wheel shaft drive	4-wheel shaft drive	6-wheel shaft drive	4-wheel shaft drive	4-wheel shaft drive
Suspension							
Front Details	Adjustable Dual A-Arms	Adjustable Dual A-Arms	Adjustable Dual A-Arms	MacPherson Strut	MacPherson Strut	Double A-Arm with antisway bar	Double A-Arm
Rear Details	Independent Rear Suspension	Independent Rear Suspension	Self-Leveling Suspension™ with Nivomat® Shocks	Independent Rear Suspension	Swingarm Dual Shocks	Rolled independent with antisway bar	Rolled independent with antisway bar
Front Suspension	9.63 in. Dual A-Arm/24.5 cm	9.63 in. Dual A-Arm/24.5 cm	9.63 in. Dual A-Arm/24.5 cm	8.0 in./20.32 cm	8.0 in./20.32 cm	9.0 in./22.9 cm	12 in. Fox Podium® (comp adjust/res.)/30 cm
Rear Suspension	9.0 in. Dual A-Arm/22.9 cm	9.0 in. Dual A-Arm/22.9 cm	7.5 in. Dual A-Arm/19 cm with load-leveling shocks	9.0 in./22.9 cm	6.25 in./15.9 cm	9.5 in./24 cm	12 in. Fox Podium® (comp adjust/res.)/30 cm
Center Suspension	N/A	N/A	N/A	N/A	Prog. rate, fully ind. A-Arm, 5.3 in./13.3 cm of travel	N/A	N/A
Tires (front/rear)	25 x 10-12/25 x 11-12	25 x 10-12/25 x 11-12	26 x 9-12/26 x 11-12	26 x 9-12/26 x 11-12	25 x 10-12/25 x 11-12	25 x 8-12/25 x 10-12	26 x 9-12/26 x 12-12
Dimensions							
Wheelbase	76 in./193 cm	76 in./193 cm	76 in./193 cm	108 in./274 cm	90 in./229 cm	77 in./196 cm	77 in./196 cm
Turning Radius	158 in./401 cm	158 in./401 cm	166 in./422 cm with Power Steering	224 in./567 cm	186 in./472 cm	101.5 in./258 cm	149.5 in./380 cm
Dry Weight	1,214 lbs./550 kg	1,237 lbs./561 kg	1,262 lbs./572 kg	1,460 lbs./662 kg	1,410 lbs./640 kg	945 lbs./429 kg	1,000 lbs./454 kg
Ground Clearance	12 in./30 cm	12 in./30 cm	12 in./30 cm	11 in./28 cm	7.2 in./18 cm	10 in./25 cm	12.5 in./32 cm
Length/Width/Height	113 in./60 in./75 in. (287 cm/152 cm/190 cm)	113 in./60 in./75 in. (287 cm/152 cm/190 cm)	113 in./60 in./75 in. (287 cm/152 cm/190 cm)	145 in./60 in./75 in. (368 cm/152 cm/190 cm)	120 in./60 in./75 in. (305 cm/152 cm/190 cm)	102 in./50 in./69 in. (259 cm/127 cm/75 cm)	106 in./60.5 in./70.5 in. (269 cm/154 cm/179 cm)
Brakes	4-wheel hydraulic disk	4-wheel hydraulic disk	4-wheel hydraulic disk	4-wheel hydraulic disk	4-wheel hydraulic disk	4-wheel hydraulic	4-wheel hydraulic
Parking Brake	Hand-activated	Hand-activated	Hand-activated	Hand-activated	Hand-activated	N/A	N/A
Load Capacity							
Box Dimension/Capacity	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/1,000 lbs. (454 kg)	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/1,000 lbs. (454 kg)	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/1,000 lbs. (454 kg)	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/1,000 lbs. (454 kg)	54 in. x 42.5 in. x 11.5 in. (143 cm x 108 cm x 31.5 cm)/1,250 lbs. (567 kg)	42 in. x 22 in. (107 cm x 56 cm)/300 lbs. (136 kg)	42 in. x 22 in. (107 cm x 56 cm)/300 lbs. (136 kg)
Payload Capacity	1,500 lbs./681 kg	1,500 lbs./681 kg	1,500 lbs./681 kg	1,750 lbs./794 kg	1,750 lbs./794 kg	740 lbs./336 kg	740 lbs./336 kg
Hitch Tow Capacity	1,500 lbs./681 kg	2,000 lbs./907 kg	2,000 lbs./907 kg	2,000 lbs./907 kg	2,000 lbs./907 kg	1,500 lbs./681 kg	1,500 lbs./681 kg
Cargo System	Lock & Ride®	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Seating	3	3	3	6	3	2	2
Skid Plate	Full	Full	Full	Full	Full	Full	Full